

ECORASTER® Bloxx – with integrated drainage joints

For quick and durable permeable pavement



Technical specifications

Dimensions	13 in x 13 in x 2 in
Weight per sq ft.	17.4 lbs
Weight per unit	20.8 lbs
Carrying load	Exceeds H90 and HL92 (fill/base dependent)
Dimensional stability	Temperature range -58°F to +194°F
Concrete dimensions	5.6 in x 5.6 in x 1.75 in
Pressure resistance	Up to 20 t axle load in acc. with DIN 1072
Material	100% recycled LDPE and concrete
Available colors	Natural, black, red, grey

Advantages

- ✓ High performance permeable paving
- ✓ Weather and salt resistant
- ✓ High load
- ✓ Very high infiltration rate
- ✓ Resistant to UV and aggressive solvents
- ✓ Seamless fit with other Ecoraster systems
- ✓ Proven safety locking system
- ✓ Made from 100% recycled LDPE
- ✓ German design
- ✓ Environmentally neutral
- ✓ Versatile applications
- ✓ Minimal maintenance

Most suitable for

Stormwater Management

- Parking lots and driveways with snow conditions
- Emergency and fire access lanes
- Outdoor warehousing and logistic areas
- Soft shoulder reinforcement
- Streetcar track fill reinforcement
- Roads
- Oil and mining applications
- Pools and decks
- Accessible paths and sidewalks



JEFF RUTHERFORD

Director & VP Operations

403.512.7261

jrutherford@crocindustries.com

Bay 1, 261065 Wagon Wheel Way
Rocky View County, AB T4A 0E2

www.crocindustries.com

801 Tremaine Ave. S. PO Box 53
Listowel ON, N4W 3H2
info@purus-northamerica.com
800 495 5517

 **ECORASTER®**

www.purus-northamerica.com